




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B62B 3/02, B62D 51/04	A1	(11) International Publication Number: WO 95/20514 (43) International Publication Date: 3 August 1995 (03.08.95)
(21) International Application Number: PCT/SE94/01270 (22) International Filing Date: 30 December 1994 (30.12.94) (30) Priority Data: 9400238-3 26 January 1994 (26.01.94) SE (71) Applicant (for all designated States except US): S. BERENDSEN AB [SE/SE]; P.O. Box 60029, S-216 10 Malmö (SE). (72) Inventors; and (75) Inventors/Applicants (for US only): ANDRÉEN, Gunnar [SE/SE]; Petters väg 8, S-245 63 Hjärrup (SE). BERIX, Leif [SE/SE]; Överby Berg, S-461 70 Trollhättan (SE). (74) Agent: AWAPATENT AB; P.O. Box 5117, S-200 71 Malmö (SE).		(81) Designated States: AM, AT, AT (Utility model), AU, BB, BG, BR, BY, CA, CH, CN, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, ES, FI, FI (Utility model), GB, GE, HU, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SI, SK, SK (Utility model), TJ, TT, UA, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i> <i>In English translation (filed in Swedish).</i>

(54) Title: MOTOR-DRIVEN TROLLEY**(57) Abstract**

A trolley (B), which is adapted to be connected to a wheel-mounted loading trolley (A), has idle wheels (2, 2a) on which it can be wheeled by hand, either alone or together with the loading trolley (A). The trolley (B) further has a motor-driven wheel (4). The wheel (4) and the associated motor (3) are fixed to a tube (9) which is vertically displaceable and rotatably mounted in the chassis (13) of the trolley (B). By an operating handle (10), the tube (9) can be vertically displaced in the chassis (13). The operating handle (10) is articulated to the tube (9) and the chassis (13) by means of a dead-centre elbow mechanism (11). In the one stable position of the elbow mechanism (11), the motor-driven wheel (4) has floor contact in order to drive the trolley (B) and the loading trolley (A), if connected thereto. In the other stable position of the elbow mechanism (11), only the idle wheels (2, 2a) of the trolley (B) have floor contact when the trolley (B) is connected to the loading trolley (A).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

MOTOR-DRIVEN TROLLEY

This invention relates to a motor-driven trolley which is intended to be connected to a wheel-mounted loading trolley in order to drive the latter.

EP-B1-0 281 536 discloses a laundry trolley for use at hotels, hospitals and the like. This trolley is designed for use as a cleaning trolley, one or more removable sections for the cleaning articles being then applied to the trolley. The section or sections are preferably equipped with wheels, as is the trolley itself (in the following referred to as the loading trolley).

The use of such section-equipped loading trolleys has created a need for facilitating their displacement. To this end, such a section is provided with a motor which is so arranged, according to one aspect of the invention, that the section (in the following referred to as the motor-driven trolley) is easily and expediently connectible to the loading trolley and that the assembly consisting of the loading trolley and the motor-driven trolley is easily driven with the aid of the motor-driven trolley. Another, secondary, aspect of the invention is that the motor-driven trolley should itself be movable by motor operation and that it should be possible to wheel by hand not only the motor-driven trolley but also the assembly consisting of the loading trolley and the motor-driven trolley.

The objects of the invention are achieved by means of the trolley according to the claims.

The invention will now be described in more detail with reference to the accompanying drawings, in which

Figs 1A and B and 2A and B illustrate the inventive concept, and

Fig. 3 shows an arrangement for moving the driving wheel of the motor-driven trolley between two stable positions.

Figs 1A and B and 2A and B, which illustrate the inventive concept, show an undriven loading trolley A having four castor wheels 1, as well as an inventive motor-driven trolley B having two fixed wheels 2 and two castor wheels 2a. The motor-driven trolley B has a battery-powered motor 3 and a wheel 4 fixed to the output shaft thereof. The

motor-driven trolley B can be mechanically connected to the loading trolley A in order to drive the latter. The wheel 4 with the associated motor 3 is vertically displaceable in the motor-driven trolley B, such that it can be brought into engagement with the floor C, which
5 enables the motor-driven trolley B and the loading trolley A connected thereto to be driven on the floor C (Fig. 1B), in which case the wheels 2, 2a of the motor-driven trolley have no floor contact. When the wheel 4 is drawn up, the motor-driven trolley B and the loading trolley A optionally connected thereto can be wheeled by hand on the
10 floor C on the wheels 1, 2a, 2 (Figs 1A and 2B), or preferably on the wheels 1 only when interconnected, which makes it easier to cross thresholds because the trolley B is hanging freely on the loading trolley A, in which case e.g. the wheels 2, 2a may have a suspension of shorter length than the one shown in the Figures. As appears from
15 the drawings, the wheel 4 is arranged behind the wheels 2, 2a at the back of the motor trolley B. When the wheel 4 is in the lower position (the driving position), also the castor wheels 2a can thus have floor contact, so that the motor-driven trolley B can be driven separately (Fig. 2A).

20 In view of the mechanical interconnection of the trolleys A and B, the motor-driven trolley B is provided with hooks 5, 6, and the trolley A is provided with pockets or rods 7, 8. The hook 5 is articulated and preferably spring-loaded, such that the hook 6 is first brought into engagement with a pocket or rod 7 (after tilting the motor-driven
25 trolley B clockwise, as seen in Figs 1 and 2), and the hook 5 is then brought into engagement with a pocket or rod 8. EP-B1-0 281 536 describes such an interconnection arrangement, as well as other such arrangements that might be used.

The vertical displacement of the wheel 4 and the associated
30 motor 3 is brought about with the aid of a tube 9 fixedly connected to the wheel 4 and the motor 3, an operating handle 10 and a dead-centre elbow mechanism 11 (see Fig. 3) interconnecting the tube 9 and the handle 10. The operating handle 10 is articulated to the tube 9 at 12 and to a tube 14 by means of a link 15. In the tube 14, which
35 is fixedly connected to the chassis 13 (which carries the wheels 2, 2a) of the motor-driven trolley, the tube 9 can be vertically displaced as well as rotated about its longitudinal axis. For enabling the trolley A

to be driven on an even floor C from the stable end position shown in Fig. 1A (all the wheels 1, 2, 2a, or merely the wheels 1, having floor contact), the elbow mechanism 11 passes from a position in which the handle 10 is vertical (dash-dot line 10'; the centre axis) to a position
5 in which the handle 10 has been turned through 90° (dash-dot line 10'') in which the wheels 2, 2a have been moved out of previous floor contact, if any, a dead-centre position having been passed, as indicated by the dash-dot link 15.

The stroke length of the tube 9 can be suitably set by having the
10 point of articulation 16 of the link 15 on the tube 14 arranged on a stop bushing 17, which is vertically displaceable on the tube 14 and can be fixed in the set vertical position and which further can rotate round the tube 14 to enable rotation of the wheel 4, such that the trolley A can be moved in different directions.


15 An electric wire 18 running through the tube 9 connects electric control means 19 provided on the handle 10 with the motor 3 via control electronics 20 for the motor 3. The control electronics 20 may, inter alia, be adapted to adjust the speed and reverse the motor 3. There are further provided a chargeable battery 21 and a battery
20 charger 22, which is charged from a wall socket by means of an electric wire 23.

CLAIMS

1. A trolley (B) which is adapted to be connected to a wheel-
5 mounted loading trolley (A) and which has idle wheels (2, 2a) and
connecting means (5, 6) for said connection, c h a r a c t e r -
i s e d in that
- the trolley (B) further has a motor-driven wheel (4),
 - the motor-driven wheel (4) and its motor (3) are fixed to a tube
10 (9),
 - the tube (9) is vertically displaceable and rotatably mounted
in the chassis (13) of the trolley (B),
 - the tube (9) has an operating handle (10) for vertical displace-
ment of the tube (9) in the chassis (13), and
 - 15 - the operating handle (10) is articulated to the tube (9) and the
chassis (13) by means of a dead-centre elbow mechanism (11);
 - the motor-driven wheel (4) having, in the one stable position
of the elbow mechanism (11) but not in the other, floor contact in
order to drive the trolley (B) and the loading trolley (A) connected
20 thereto.
2. A trolley as set forth in claim 1, c h a r a c t e r i s e d
in that the connecting means (5, 6) or the idle wheels (2, 2a) and the
elbow mechanism (11) are so arranged that, when the trolley (B) is
connected to the loading trolley (A), the other stable position of the
25 elbow mechanism (11) does not permit floor contact for any of the
wheels (2, 2a, 4) of the trolley (B).
3. A trolley as set forth in claim 1 or 2, c h a r a c t e r -
i s e d in that the tube (9) can rotate in the chassis (13) of the trolley
(B).
- 30 4. A trolley as set forth in any one of claims 1-3, c h a r a c -
t e r i s e d in that the motor-driven wheel (4) is so positioned that
the trolley (B) itself can be motor-driven on the motor-driven wheel (4)
and on at least two (2a) of the idle wheels.

2/2

FIG. 3



INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 94/01270

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: B62B 3/02, B62D 51/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: B62B, B62D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	FR, B1, 2120301 (LEBRE, CHARLES), 18 August 1972 (18.08.72) --	1
A	FR, A1, 2595650 (ROMANO, ROBERT), 18 Sept 1987 (18.09.87) --	1
A	GB, A, 2049577 (THE ROYAL BOROUGH OF KENSINGTON AND CHELSEA), 31 December 1980 (31.12.80) --	1
A	US, A, 1116295 (P. KLECKNER), 3 November 1914 (03.11.14) -- -----	1

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

Date of mailing of the international search report

5 April 1995

23 -05- 1995

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Göran Carlström

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT
Information on patent family members

25/02/95

International application No.

PCT/SE 94/01270

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
FR-B1- 2120301	18/08/72	NONE	
FR-A1- 2595650	18/09/87	NONE	
GB-A- 2049577	31/12/80	NONE	
US-A- 1116295	03/11/14	NONE	